PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2002-371121

(43) Date of publication of application: 26.12.2002

(51)Int.CI.

CO8G 18/66 B24B 37/00

H01L 21/304

(21)Application number: 2002-105459

(71)Applicant: TOYOBO CO LTD

TOYO TIRE & RUBBER CO LTD

(22)Date of filing:

08.04.2002

(72)Inventor: MASUI TAKASHI

ONO KOICHI

OGAWA KAZUYUKI SEYANAGI HIROSHI

(30)Priority

Priority number : 2001110265

Priority date: 09.04.2001

Priority country: JP

(54) POLISHING PAD COMPRISING POLYURETHANE COMPOSITION

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a polishing pad capable of overcoming the problems of providing bad effects to smoothing processing caused by the change of the hardness (modulus) of the polishing pad by the frictional heat between the polishing pad and an article to be processed at the time of polishing, and capable of stably carrying out the smoothing processing in wide temperature range.

SOLUTION: This polishing pad is made of a polyurethane obtained from an organic polyisocyanate, a polyol and a curing agent, as a main component. The curing agent is 4,4'-methylene-bis(ochloroaniline), and the polyol is a polytetramethylene glycol having a 500-1,600 number average molecular weight and <1.9 molecular weight distribution (weight average molecular weight/ number average molecular weight).

LEGAL STATUS

[Date of request for examination]

09.05.2002

[Date of sending the examiner's decision of

rejection]

[Kind of final disposal of application other than

the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3359629

[Date of registration]

11.10.2002

[Number of appeal against examiner's decision of

rejection]

[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office